

KIOTI
run ahead of the pack

KIOTI PREMIUM TRACTOR
DK754C/DK904C



Specifications

MODEL	DK754C	DK904C	DK754C	DK904C
ENGINE				
Model	1104D-44T (Tier 3)			
Engine Gross Power	HP(kW)	74.4(55.5)@2200	91.2(68)@2200	
Displacement	cc(cu)	4400		
Rated revolution	rpm	2200		
Fuel tank capacity	ℓ (us gal)	125		
TRANSMISSION				
Type	Full synchromesh			
- No. of speeds	16 Forward, 16 Reverse			
Diff. Lock	Rear (standard)			
Front wheel drive system	Hydraulic			
Traveling speed				
- Forward	Km/h(mph)	1st-0.22, 16th-31.89		
- Reverse	Km/h(mph)	1st-0.19, 16th-28.39		
BRAKES & CLUTCH				
Brakes	Wet Disc (Hydraulic)			
Clutch	Dry single plate-single stage Type<Ceramic type>			
Clutch Size	mm(in.)	325		
POWER TAKE-OFF				
Type	Independent / Ground			
PTO revolution	RPM	540 / 1000		
3-POINT HITCH				
Type	Category II			
Lift Capacity at lift point	kg.f(lbs)	2400(max)		
Drawbar type	Swing drawbar			
Top Link	Ball type			
Lower Link	Cassette type			
HYDRAULICS				
Pump Capacity	ℓ /min	1st : 46.5(21.14cc) 2nd : 37.1(16.85cc)		
3-pt. Hitch control	Position, Draft and mixed Control			
Steering	Hydrostatic			
STANDARD TIRES(Agri Tire)				
- Front	12.4-24			
- Rear	18.4-30			
DIMENSIONS				
Length (with front weight)	mm(in.)	4537		
Width	mm(in.)	2005		
Height	mm(in.)	2750		
Wheelbase	mm(in.)	2310		
Ground Clearance	mm(in.)	418		
Front Tread-Std. Tires	mm(in.)	1520		
Rear Tread-std. Tires	mm(in.)	1535		
Weight	kg.f(lbs)	3525		



**Kioti Tractor/
Daedong Industrial. Co., Ltd.**
1422-5, Seocho-Dong, Seocho-Ku, Seoul, Korea
tel 82-2-3470-7454~9 • fax 82-2-3470-7485
web www.daedong.co.kr

Dealer Imprint Area

Kioti Tractor / Daedong Ind. Co., Ltd. / 2008.01(EU)

