

IMPRESS

Baler & wrapper combinations



The advantages at a glance.

Maximum versatility

High capacity wrapping, hassle free bale transfer and bale grouping. An innovative, fast, high throughput wrapper to match the high output baler. Adjustable wrapping satellites for bale diameters between 3.61 ft / 1.10 m and 4.92 ft / 1.50 m (155 VC).

Forage quality

Bale and wrap in one pass. The best forage quality thanks to the finished bale being wrapped immediately.

Reliability

A compact design with twin satellite arms mounted from under the table. Wrap pre-stretch units with wrap break monitor and are easily adjusted to 50% or 70% pre-stretch. Rapid and reliable bale transfer on slopes up to 40% with secure bale transfer unit onto the wrapper table.

Convenience

Fully automatic adjustable wrapping system that operates at high working speeds. Choose between automatic and manual mode. Convenient controls at the rear for maintenance and service work. Hydraulic folding wrap storage is protected inside the bodywork.



IMPRESS 125 FC PRO / IMPRESS 155 VC PRO



- 1 Bale transfer on slopes of up to 40%
- 2 Twin arm satellite wrapper unit is mounted from below.
- 3 Wrap pre-stretch unit
- 4 Wrap storage protected behind bodywork



Technical data

| IMPRESS | 125 FC PRO | 155 VC PRO |
|--------------------------|--|--|
| Bale diameter | 4.10 ft / 1.25 m | 2.6 – 5.1 ft / 0.80 – 1.55 m |
| Bale width | 3.93 ft / 1.20 m | 3.93 ft / 1.20 m |
| Pick-up width | 7.54 ft / 2.30 m | 7.54 ft / 2.30 m |
| Maximum No. of knives | 32 | 32 |
| Knife spacing | 1.41 inch / 36 mm | 1.41 inch / 36 mm |
| Tractor PTO speed | 1000 rpm | 1000 rpm |
| Power requirement from | 96 kW / 130 hp | 96 kW / 130 hp |
| Hydraulic power required | 60 l/min, 180 bar 13 gal / min, 180 bar | 60 l/min, 180 bar 13 gal / min, 180 bar |
| Wrap pre-stretch | 50 / 70 % | 50 / 70 % |
| Wrap roll storage | 12 rolls | 12 rolls |
| Length | 23.8 ft / 7.24 m | 23.8 ft / 7.24 m |
| Width | 9.48 ft / 2.89 m | 9.48 ft / 2.89 m |
| Height | 8.37 ft / 2.55 m | 9.27 ft / 2.83 m |
| Tandem tyres | 500/60R22.5 | 500/60R22.5 |
| Weight | 16622 lbs / 7540 kg | 16622 lbs / 7540 kg |

IMPRESS technology highlights

- Pendular pick-up for the best ground tracking.
- LIFTUP rotor offers, tangential crop flow into bale chamber.
- FLEXCUT chopping system with 32 reversible TWIN BLADE knives.
- Variable knife group switching, individual knife protection system.
- Pull-out EASY MOVE knife bank.
- Net wrap with adjustable feed unit.
- Compact wrapper unit with twin satellites mounted from below.
- Wrap break monitors.
- Convenient controls at rear for all wrapper functions and hydraulic fold out of wrap storage system.
- LED floodlights, flashing beacon and camera.
- Automatic lubrication of all chain drives.
- All roller bearings (both fixed and variable chamber models) are lubricated via progressive greasing.
- Convenient operation, ISOBUS compatible and numerous automatic features.

All information and images relating to technical data, dimensions, weights, output, etc. are approximate and are not binding.